



## HOBO<sup>®</sup> U22-001 Data Logger

### Water Temperature Pro v2

The HOBO Water Temp Pro v2 is durable with 12-bit resolution. Complete with a precision sensor for  $\pm 0.2^{\circ}\text{C}$  accuracy, this logger measures temperatures between  $-40^{\circ}\text{C}$  and  $70^{\circ}\text{C}$  ( $-40^{\circ}\text{F}$  to  $158^{\circ}\text{F}$ ) in air and up to  $50^{\circ}\text{C}$  ( $122^{\circ}\text{F}$ ) in water. Its waterproof, streamlined case allows for extended deployment in fresh or salt water. Moreover, the Water Temp Pro v2's optical USB interface makes it possible to offload data even while the logger is wet or underwater. A solar radiation shield is required to obtain accurate air temperature measurements in sunlight (RS1 Solar Radiation Shield, assembly required; or M-RSA pre-assembled Solar Radiation Shield).



#### Key Advantages:

- Research-grade measurements at an affordable price
- Waterproof to 120 meters (400 feet)
- Data readout in less than 30 seconds via fast Optic USB interface
- Compatible with HOBOWare and HOBOWare Pro software for logger setup, graphing and analysis

## HOBO U22-001 Data Logger Specifications

**Operation range**<sup>†</sup>: -40° to 70°C (-40° to 158°F) in air; maximum sustained temperature of 50°C (122°F) in water

**Accuracy**: ±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F)

**Resolution**: 0.02°C at 25°C (0.04°F at 77°F)

**Response time**: (90%) 5 minutes in water; 12 minutes in air moving 2 m/sec (typical)

**Stability (drift)**: 0.1°C (0.18°F) per year

**Real-time clock**: ± 1 minute per month 0° to 50°C (32° to 122°F)

**Battery**: 2/3 AA, 3.6 Volt Lithium, factory-replaceable ONLY

**Battery life (typical use)**: 6 years with 1 minute or greater logging interval

**Memory (non-volatile)**: 64K bytes memory (approx. 42,000 12-bit temperature measurements)

**Weight**: 42 g (1.5 oz)

**Dimensions**: 3.0 cm (1.19 in.) maximum diameter, 11.4 cm (4.5 in.) length; mounting hole 6.3 mm (0.25 inches) diameter

**Wetted materials**: Polypropylene case, EPDM® o-rings, stainless steel retaining ring

**Buoyancy (fresh water)**: +13 g (0.5 oz.) in fresh water at 25°C (77°F); +17 g (0.6 oz.) with optional boot

**Waterproof**: To 120 m (400 ft.)

**Shock/drop**: 1.5 m (5 ft.) drop at 0°C to 70°C (32°F to 150°F)

**Logging interval**: Fixed-rate or multiple logging intervals, with up to 8 user-defined logging intervals and durations; logging intervals from 1 second to 18 hours. Refer to HOBOWare software manual.

**Launch modes**: Immediate start and delayed start

**Offload modes**: Offload while logging; stop and offload

**Battery indication**: Battery voltage can be viewed in status screen and optionally logged in datafile. Low battery indication in datafile.

**NIST certificate available**: for additional charge

**Environmental Rating**: IP68

The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).

<sup>†</sup>**IMPORTANT**: The plastic case will become brittle at temperatures lower than -20°C. If the logger is deployed in a location where the temperature drops below -20°C, make sure the logger remains stationary and is not pulled on or struck. Return the logger to above -20°C before handling.

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532