

Mist Guard Cooling

Controls mist for the climate you need



- High-precision Temperature and Humidity sensors
- Up to 10 valves in sequence
- Misting according temperature and humidity
- Event logbook



Controls mist for the climate you need

Misting applications


- Up to 10 valves 24VAC OR single valve DC Latch
- Built-in precision temperature and humidity sensors
- Advanced control of Booster Pump and Pressure Relief Valve
- Logs temperature and humidity (min & max), and event logbook

Two misting methods:

- Dual-Mist above temperature or below humidity thresholds.
- Heat-Mist above dynamic temperature influenced by humidity

Hardware and Software specifications

- Battery operated 2AA Alkaline for DC Latch Solenoid
- Requires 24VAC/1Amp power supply for 10 outputs
- High-precision temperature sensor -50°C (-58°F) to +50°C (122°F), $\pm 0.25^{\circ}\text{C}$ ($\pm 0.45^{\circ}\text{F}$)
- High-precision humidity sensor 0-100%, $\pm 2\%$
- Logs min and max temperature and humidity levels over the last 24-hours
- 480-events logbook includes time and date stamping
- Displays Celsius, Fahrenheit, Relative Humidity and Dew Point readings



02-0406-CMTFBR-0179-EN

Graff Visual Communications / www.graff.co.il



Headquarters: Netafim Ltd.

161 Arlozorov St. Tel Aviv 64922, Israel

Tel:+972 3 6919777 ■ Fax:+972 3 6911962 ■ postmaster@netafim.com ■ www.netafim.com

Crop Management Technology Division

Tel:+972 4 6287563 ■ Fax:+972 4 6287717 ■ CMT@netafim.com

